

# Shell tellus 33 specs

shell tellus 33 specs The Shell Tellus 33 is a high-quality hydraulic oil renowned for its reliable performance, advanced formulation, and suitability for a wide range of industrial applications. As part of Shell's extensive range of lubricants, the Tellus 33 is specifically engineered to meet the demanding needs of hydraulic systems, ensuring smooth operation, protection against wear, and efficient energy transfer. Understanding the specifications of Shell Tellus 33 is essential for engineers, maintenance professionals, and equipment operators seeking optimal performance and longevity of their machinery. This in-depth article explores the detailed specifications of Shell Tellus 33, including its technical properties, performance standards, applications, and benefits.

### Overview of Shell Tellus 33

Shell Tellus 33 is a mineral-based hydraulic oil formulated with advanced additives to deliver excellent lubrication, oxidation stability, and corrosion protection. It is designed to operate efficiently across a broad temperature range and under varying load conditions, making it a versatile choice for hydraulic systems in construction, manufacturing, and mobile equipment.

### Technical Specifications of Shell Tellus 33

Understanding the technical specifications of Shell Tellus 33 provides insight into its performance capabilities and compatibility with different machinery.

#### Physical and Chemical Properties

The key physical and chemical properties of Shell Tellus 33 include:

- Viscosity at 40°C: Approximately 33 cSt (centistokes)
- Viscosity at 100°C: Around 6.0 cSt
- Density at 15°C: About 0.88 g/cm<sup>3</sup>
- Flash Point (COC): Typically over 200°C, ensuring safety during handling and storage
- Pour Point: Usually around -21°C, indicating good low-temperature performance
- Fire Point: Exceeds 220°C

### Performance Standards and Approvals

Shell Tellus 33 meets or exceeds several international standards and specifications, ensuring its suitability for various applications:

- ISO 11158: Type HM (Hydraulic Mineral Oil)
- DIN 51524 Part 2: HVLP (High Viscosity, Low Pour Point)
- Denison HF-0 / HF-2 / HF-4: Approved, indicating compatibility with Denison hydraulic systems
- ISO 6743-4: Hydraulic fluids, HM category
- API Service Classification: Suitable for industrial hydraulic systems requiring a high-performance mineral oil

### Viscosity and Temperature Range

The viscosity of Shell Tellus 33 is a critical factor influencing its performance and application scope.

#### Viscosity Grades and Selection

Shell Tellus 33, as indicated by its name, has a viscosity of approximately 33 cSt at 40°C, making it suitable for systems requiring medium viscosity oils. The viscosity index (VI) of the product indicates its stability across temperature variations, with typical values around 95-100, which helps maintain consistent film thickness in the hydraulic system.

#### Operational Temperature Range

The oil's pour point of -21°C and high flash point over 200°C allow it to operate efficiently in cold climates and high-temperature environments. It maintains good flow characteristics at low temperatures and provides sufficient thermal stability at elevated temperatures, ensuring reliable system performance.

### Performance Characteristics of Shell Tellus 33

The effectiveness of Shell Tellus 33 is derived from its advanced formulation and additive package, which provide numerous performance advantages.

#### Oxidation Stability

The oil resists oxidation and sludge formation, extending the service life of hydraulic systems and reducing maintenance costs. Its high oxidation stability minimizes deposit formation, which can impair system efficiency.

#### Wear Protection

Additives in Shell Tellus 33 form protective films on moving parts,

reducing metal-to-metal contact and wear. This enhances component lifespan and reduces downtime.

### Corrosion and Rust Inhibition

The product contains corrosion inhibitors that protect hydraulic system components from rust and corrosion, especially in humid or contaminated environments.

### Foam Control and Air Release

Shell Tellus 33 exhibits excellent foam control properties and air release characteristics, vital for maintaining hydraulic efficiency and preventing cavitation.

### Applications of Shell Tellus 33

Shell Tellus 33 is suitable for a broad array of hydraulic systems, owing to its balanced viscosity and performance traits.

### Industrial Machinery

Manufacturing presses  
Conveyor systems  
Machine tools  
Mobile Equipment  
Construction machinery  
Agricultural equipment  
Material handling vehicles  
Marine and Offshore

### Hydraulic systems in ships

Offshore platform machinery  
Specialized Systems

### Hydraulic presses

Lift systems  
Excavators

### Benefits of Using Shell Tellus 33

Choosing Shell Tellus 33 offers several advantages that contribute to the efficiency and longevity of hydraulic systems.

#### Extended Oil Life:

High oxidation stability reduces oil degradation over time.

#### Enhanced Equipment Protection:

Superior wear and corrosion resistance safeguard system components.

#### Consistent Performance:

Stable viscosity across temperature ranges ensures reliable operation.

#### Energy Efficiency:

Reduced internal friction leads to lower energy consumption.

#### Environmental Safety:

Meets safety standards with high flash point and low volatility.

### Compatibility and Maintenance Considerations

Proper compatibility and maintenance are vital for maximizing the benefits of Shell Tellus 33.

#### System Compatibility

Compatible with most hydraulic system materials, including seals, hoses, and metals. Recommended for use in systems requiring ISO 11158 HM type oils.

#### Oil Change and Monitoring

Follow manufacturer guidelines for oil change intervals. Regularly monitor viscosity, contamination, and additives to ensure optimal performance. Use filters designed for hydraulic oils to remove debris and water contamination.

### Conclusion

Shell Tellus 33 is a high-performance hydraulic oil that combines robust technical specifications with proven performance standards. Its viscosity profile, oxidation stability, wear protection, and compatibility make it an ideal choice for diverse industrial and mobile applications. By understanding the detailed specifications of Shell Tellus 33, users can ensure their hydraulic systems operate efficiently, reliably, and with extended service life. Whether in manufacturing plants, construction sites, or marine environments, Shell Tellus 33 offers the performance and protection necessary to meet demanding operational requirements.

### Shell Tellus 33 Specs: An In-Depth Review of Its Performance and Applications

When it comes to hydraulic fluids, selecting the right lubricant is crucial for ensuring optimal performance, equipment longevity, and safety. Among the myriad options available, Shell Tellus 33 stands out as a premium hydraulic oil trusted by industries worldwide. This comprehensive review dives deep into the specifications, properties, applications, and benefits of Shell Tellus 33, providing an extensive understanding for engineers, maintenance teams, and procurement professionals.

#### Introduction to Shell Tellus 33

Shell Tellus 33 is a high-quality, anti-wear hydraulic oil formulated to meet the demanding needs of modern hydraulic systems. It is designed to deliver excellent lubrication, oxidation stability, and cleanliness, thereby extending equipment life and reducing downtime.

#### Key

**Highlights:** Developed by Shell, a leading global lubricant manufacturer. Suitable for a broad range of hydraulic applications. Meets or exceeds industry standards such as ISO 32 and DIN 51524 Part 2.

**Physical and Chemical Properties of Shell Tellus 33**

**Understanding the physical and chemical attributes of Shell Tellus 33** provides insight into its performance capabilities.

**Viscosity**

**Kinematic Viscosity at 40°C:** Approximately 33 mm<sup>2</sup>/s (centistokes).

**Viscosity Grade:** ISO 32 (indicating its viscosity class).

**Viscosity Index (VI):** Typically around 100, reflecting good viscosity stability across temperature variations. This viscosity level allows the oil to provide effective lubrication while ensuring system responsiveness, especially suitable for moderate to high-pressure hydraulic systems.

**Density and Specific Gravity**

**Density at 15°C:** ~0.88 g/cm<sup>3</sup>.

**Specific Gravity:** About 0.88, aiding in predicting flow and lubrication characteristics.

**Flash Point and Fire Resistance**

**Flash Point:** Typically above 200°C (392°F), indicating good thermal stability and safety during operation.

**Fire Resistance:** Meets industry safety standards, suitable for environments with stringent fire safety requirements.

**Oxidation and Thermal Stability**

Designed to resist oxidation, thereby minimizing sludge and deposit formation. Maintains stability under high temperature operation, ensuring consistent performance over extended periods.

**Demulsibility and Water Separation**

Exhibits excellent water separation properties, vital for hydraulic systems prone to moisture exposure. Quick separation of water from oil reduces corrosion risks and hydraulic system contamination.

**Anti-wear and Additive Content**

Contains anti-wear additives to protect system components under boundary lubrication conditions. Incorporates rust and oxidation inhibitors for enhanced equipment protection.

**Industry Standards and Approvals**

Shell Tellus 33 conforms to several international standards, confirming its quality and compatibility:

- ISO 11158: Hydraulic fluid classification ISO 32.
- DIN 51524 Part 2: Lubricant for hydraulic systems.
- AGMA 9005-E02: Suitable for industrial gear oils.
- ASTM D6158: Performance in hydraulic applications.

**Compatibility:** Compatible with various pump materials, seals, and hoses.

**Applications of Shell Tellus 33**

Given its versatile properties, Shell Tellus 33 is suited for a wide array of hydraulic systems across multiple industries.

- Industrial Hydraulic Systems**
- Manufacturing equipment**
- Machine tools**
- Steel mills**
- Construction machinery**
- Agricultural Machinery**
- Tractors and harvesters**
- Hydraulic lifts and loaders**
- Mobile Equipment**
- Excavators**
- Cranes**
- Material handling equipment**
- Marine and Offshore**
- Hydraulic controls on ships**
- Offshore drilling platforms**
- Steel and Mining Industries**
- Hydraulic presses**
- Conveyors**
- Crushers**

**Performance Benefits of Shell Tellus 33**

Choosing Shell Tellus 33 offers numerous advantages that contribute to efficient and reliable hydraulic system operation.

- Enhanced Equipment Longevity** The anti-wear additives prevent metal-to-metal contact.
- Oxidation stability** reduces deposit formation, protecting pumps and valves.
- Operational Efficiency** Stable viscosity across temperature ranges ensures consistent hydraulic response.
- Good demulsibility** minimizes water contamination, reducing corrosion and wear.
- Cost-Effectiveness** Longer oil drain intervals due to oxidation stability.
- Reduced maintenance costs and downtime.**
- Environmental and Safety Compliance** Meets safety standards with high flash points.
- Formulated with environmentally considerate additives.**

**Usage Guidelines and Maintenance**

Proper handling and maintenance optimize the performance of Shell Tellus 33.

**Storage Recommendations:** Store in clean, dry, and covered containers. Protect from extreme temperatures and contamination.

**Application Tips:** Use compatible filters and seals to prevent contamination. Follow recommended oil change intervals as

per equipment manufacturer guidelines. Monitoring and Testing: Regularly check viscosity, water content, and cleanliness. Conduct oil analysis to track additive depletion and contamination levels. Comparison with Other Hydraulic Oils While Shell Tellus 33 is highly regarded, understanding how it stacks against competitors is valuable.

| Aspect              | Shell Tellus 33          | Competitor A | Competitor B |
|---------------------|--------------------------|--------------|--------------|
| Viscosity Grade     | ISO 32                   | ISO 32       | ISO 32       |
| Oxidation Stability | Excellent                | Good         | Fair         |
| Water Separation    | Fast                     | Moderate     | Slow         |
| Additive Package    | Advanced anti-wear       | Basic        | Moderate     |
| Compatibility       | Broad (seals, materials) | Limited      | Moderate     |

This comparison highlights Shell Tellus 33's superior oxidation stability and water separation, making it a preferred choice in demanding applications.

Environmental and Regulatory Considerations Shell is committed to sustainability and environmental responsibility. Shell Tellus 33 complies with:

- VOC Regulations: Low volatility to reduce emissions.
- REACH Compliance: Meets European chemical safety standards.
- Disposal Guidelines: Should be disposed of following local environmental regulations to prevent pollution.

Conclusion: Why Choose Shell Tellus 33? Shell Tellus 33 embodies a blend of high-quality formulation, proven performance, and industry compliance. Its optimal viscosity, excellent stability, and robust additive package make it suitable for a wide range of hydraulic systems, from industrial machinery to mobile equipment.

Key reasons to select Shell Tellus 33:

- Ensures smooth, efficient hydraulic operation.
- Extends equipment lifespan through superior wear and oxidation protection.
- Reduces maintenance costs and downtime.
- Meets stringent international standards for safety and performance.

Investing in Shell Tellus 33 means prioritizing reliability, safety, and efficiency—a choice that pays dividends over the lifespan of your hydraulic systems.

In summary, whether you're operating heavy machinery, maintaining industrial systems, or managing mobile equipment, understanding the detailed specifications of Shell Tellus 33 helps in making informed decisions. Its well-balanced properties, compliance with global standards, and proven track record position it as a top-tier hydraulic oil for diverse applications.

QuestionAnswer

What are the main specifications of the Shell Tellus 33 hydraulic oil?

Shell Tellus 33 is a high-quality anti-wear hydraulic oil formulated with mineral base oils and advanced additives, featuring a viscosity of approximately 33 cSt at 40°C, suitable for a wide range of hydraulic systems.

What applications is Shell Tellus 33 suitable for?

Shell Tellus 33 is ideal for industrial hydraulic systems, mobile equipment, and machinery that require a stable, anti-wear hydraulic fluid with good oxidation stability and corrosion protection.

What is the viscosity grade of Shell Tellus 33?

Shell Tellus 33 has a viscosity grade of ISO 46, corresponding to its approximate kinematic viscosity of 33 cSt at 40°C.

Does Shell Tellus 33 provide anti-wear protection?

Yes, Shell Tellus 33 contains anti-wear additives that help protect hydraulic system components from wear and extend equipment life.

Is Shell Tellus 33 compatible with other hydraulic oils?

Compatibility depends on the specific oils involved; generally, Shell recommends thorough testing before mixing with other hydraulic fluids to ensure performance and prevent system issues.

What are the key performance benefits of using Shell Tellus 33?

Key benefits include excellent wear protection, good oxidation stability, corrosion prevention, and good filterability, which contribute to longer equipment life and reduced maintenance costs.

What are the operating temperature ranges for Shell Tellus 33?

Shell Tellus 33 performs well within a temperature range of approximately -20°C to +80°C, maintaining fluid stability and lubrication properties within this range.

Is Shell Tellus 33 environmentally friendly?

Shell Tellus 33 is designed to meet industry standards for environmental safety, but users should follow proper disposal and handling procedures as per local regulations.

What certifications or standards does Shell Tellus 33 meet?

Shell Tellus 33 complies with various industry standards such as DIN 51524 Part 2 (HLP), ISO 6743-4 HM, and others, ensuring high-quality performance in hydraulic systems.

How often should Shell Tellus 33 be replaced or changed?

The oil change interval depends on system conditions and operating hours, but typically, Shell recommends inspecting and replacing hydraulic oil every 1,000 to 2,000 hours of operation or as specified by equipment manufacturers.

Related keywords: Shell Tellus 33, hydraulic oil, hydraulic fluid, industrial lubricant, hydraulic oil specifications, Shell lubricants, hydraulic oil viscosity, hydraulic fluid properties, industrial oils, machinery lubrication

Mobilfluid 424 oil cross reference chart

mobilfluid 424 oil cross reference chartUnderstanding the compatibility and proper replacement options for Mobilfluid 424 oil is essential for maintaining optimal hydraulic system performance. Whether you are a maintenance technician, engineer, or a vehicle enthusiast, having access to a comprehensive Mobilfluid 424 oil cross reference chart ensures that you select the right substitute fluid, prevent equipment failure, and optimize operational efficiency. This article delves into the details of Mobilfluid 424, its specifications, compatible substitutes, and how to effectively utilize a cross reference chart for your hydraulic systems.What is Mobilfluid 424 Oil?Mobilfluid 424 is a high-performance hydraulic oil specially formulated to meet the demanding needs of modern hydraulic equipment. It provides excellent wear protection, oxidation stability, and corrosion resistance, ensuring long service life and reliable operation.Key Features of Mobilfluid 424Superior Wear Protection: Reduces metal-to-metal contact, extending the life of hydraulic components.Oxidation Stability: Resists thickening and sludge formation under high-temperature conditions.Corrosion and Rust Prevention: Protects hydraulic systems from moisture-induced damage.Excellent Compatibility: Suitable for use with a wide range of hydraulic pump types.Typical ApplicationsMobilfluid 424 is used across various industries and equipment, including:Industrial hydraulic systemsMobile equipment such as excavators and loadersMarine hydraulic systemsManufacturing machineryImportance of Cross Reference ChartsA cross reference chart is a vital resource that provides information on equivalent or compatible oils from different manufacturers or product lines. It helps in:Selecting suitable substitutes when the original oil is unavailableEnsuring compatibility with existing equipmentMaintaining system performance and extending component lifespanComplying with manufacturer specificationsHaving a clear cross reference chart for Mobilfluid 424 simplifies decision-making, especially during supply shortages or when transitioning to alternative brands.Understanding Mobilfluid 424 Cross Reference ChartA typical Mobilfluid 424 oil cross reference chart includes columns listing:The original product (Mobilfluid 424)Corresponding equivalent oils from other brands or product linesImportant technical specifications such as viscosity grades, API ratings, and additive packagesNotes on application suitability and limitationsHow to Read the ChartIdentify the original product (Mobilfluid 424) details.Cross-reference with the alternative oils listed.Check for compatibility factors such as viscosity, additive compatibility, and application type.Confirm that the substitute meets your equipment's requirements.Common Cross Reference Substitutes for Mobilfluid 424Below are some of the frequently recommended oils that serve as equivalents or alternatives to Mobilfluid 424:Shell Tellus S2 VX 46Viscosity Grade: ISO 46Features: Excellent wear protection, oxidation stability, and compatibility with various hydraulic

systems. Application: Suitable for both mobile and industrial hydraulic equipment. Chevron Rando HD 46 Viscosity Grade: ISO 46 Features: High-performance anti-wear hydraulic oil, good thermal stability. Application: Heavy-duty hydraulic systems requiring ISO 46 oil. Castrol Hyspin AWS 46 Viscosity Grade: ISO 46 Features: Good wear protection, corrosion resistance, and compatibility with a wide range of equipment. Application: Industrial hydraulic systems and mobile machinery. Total Hydraulic HLP 46 Viscosity Grade: ISO 46 Features: High oxidation stability, anti-wear properties. Application: Hydraulic systems demanding high-quality oils. Mobil DTE 24 Series Viscosity Grade: ISO 46 Features: Similar additive package, designed for hydraulic systems. Application: Industrial and mobile hydraulics.

### Key Factors to Consider When Cross Referencing Oils

When selecting an alternative to Mobilfluid 424, consider the following:

- Viscosity Compatibility:** Ensure the substitute matches the viscosity grade specified by your equipment manufacturer. Typically, Mobilfluid 424 corresponds to ISO 46 or 32 grades; verify accordingly.
- Additive Compatibility:** Confirm that the additive package in the substitute oil matches or exceeds the performance of Mobilfluid 424. Look for anti-wear, antioxidant, corrosion inhibitors, and anti-foam agents.
- Equipment Specifications:** Check manufacturer guidelines for approved oils. Avoid incompatible oils that could lead to seal deterioration or reduced performance.
- Operating Conditions:** Consider temperature ranges, pressure levels, and exposure to contaminants. Select oils with appropriate viscosity and stability characteristics.
- Environmental and Safety Regulations:** Ensure the substitute oil complies with local regulations and safety standards.

### How to Use a Cross Reference Chart Effectively

To maximize the benefits, follow these steps:

- Gather Equipment Specifications:** Know your system's requirements, including viscosity, API ratings, and additive needs.
- Identify the Original Oil:** Confirm the exact specifications of Mobilfluid 424 used in your equipment.
- Consult the Cross Reference Chart:** Find oils from reputable brands that match your specifications.
- Compare Technical Data:** Check viscosity, additive packages, and compatibility notes.
- Verify Manufacturer Recommendations:** Cross-verify with equipment manuals or manufacturer support.
- Perform Compatibility Tests:** When possible, conduct small-scale tests before full-scale replacement.
- Monitor Equipment Performance:** After switching oils, observe system behavior and perform regular maintenance.

### Benefits of Using the Correct Cross Reference Oil

Using an appropriate cross-referenced oil offers several advantages:

- Prolongs Equipment Life:** Proper lubrication reduces wear and tear.
- Maintains Performance:** Consistent hydraulic pressure and responsiveness.
- Reduces Downtime:** Fewer failures and maintenance issues.
- Ensures Safety Compliance:** Meets industry safety standards.
- Cost Savings:** Avoids costly repairs and replacements.

### Frequently Asked Questions (FAQs)

**Is Mobilfluid 424 compatible with other hydraulic oils?** Yes, but compatibility depends on the specific oil's additive package and viscosity. Always refer to the cross reference chart and manufacturer specifications.

**Can I mix Mobilfluid 424 with other oils?** Mixing oils can sometimes lead to undesirable chemical interactions, reducing performance. It's best to use a compatible substitute without mixing.

**How often should I change hydraulic oils like Mobilfluid 424?** Typically, hydraulic oils should be replaced every 2,000 to 4,000 hours of operation or as recommended by the equipment manufacturer, considering operating conditions.

**What are the signs of oil degradation?** Indicators include increased system temperature, noise, sluggish operation, foaming, or visible sludge.

**Where can I find a reliable cross reference chart?** Reputable industry publications, manufacturer datasheets,

or authorized distributors often provide comprehensive cross reference charts. **Conclusion** The mobilfluid 424 oil cross reference chart is an indispensable tool for ensuring the correct selection of hydraulic oils that meet or exceed original specifications. By understanding the key features of Mobilfluid 424, recognizing suitable substitutes, and following best practices for cross referencing, you can maintain the efficiency, safety, and longevity of your hydraulic systems. Always prioritize compatibility, quality, and manufacturer recommendations when choosing alternative oils, and consult trusted resources or professionals for guidance. Maintaining the right hydraulic fluid is essential for optimal system performance. Use the cross reference chart wisely to make informed decisions, reduce operational risks, and save costs in the long run.

**Mobilfluid 424 Oil Cross Reference Chart: An In-Depth Investigation** In the world of industrial machinery and hydraulic systems, selecting the right lubricant is paramount to ensuring optimal performance, longevity, and safety. Among the myriad of options available, Mobilfluid 424 oil has garnered significant attention due to its specialized properties and application versatility. However, for engineers, maintenance professionals, and procurement specialists, understanding how Mobilfluid 424 compares to other lubricants through cross-reference charts becomes essential. This comprehensive investigation aims to shed light on the Mobilfluid 424 oil cross reference chart, exploring its composition, applications, and how it aligns with other industrial oils to facilitate informed decision-making.

**What Is Mobilfluid 424 Oil?** Before delving into cross-referencing, it's crucial to understand what Mobilfluid 424 oil is and its primary characteristics.

**Composition and Properties** Mobilfluid 424 is a high-performance, synthetic-based hydraulic fluid designed to operate under demanding conditions. Its key features include:

- Excellent thermal stability:** Maintains viscosity and performance across a broad temperature range.
- Oxidation resistance:** Reduces sludge and deposit formation.
- Corrosion and rust protection:** Safeguards metal surfaces.
- Compatibility:** Suitable for various hydraulic systems, including those with sensitive elastomers.

**Typical Applications** Mobilfluid 424 is commonly used in:

- Hydraulic systems in aerospace, mobile, and industrial equipment
- Precision machinery requiring high-quality lubricants
- Systems where environmental considerations demand low toxicity and high biodegradability

**The Importance of Cross-Reference Charts in Industrial Lubrication** In industrial maintenance and procurement, cross-reference charts serve as vital tools. These charts enable technicians and engineers to:

- Identify equivalent lubricants from different brands or series
- Ensure compatibility with existing equipment during supplier changes
- Optimize costs by substituting with more readily available or economical options without compromising performance
- Facilitate compliance with safety and environmental standards

Given the complexity of lubricant chemistry, cross-reference charts are often detailed, considering viscosity grades, additive packages, base oil types, and certifications.

**Understanding the Structure of the Mobilfluid 424 Cross Reference Chart** A typical Mobilfluid 424 oil cross reference chart includes several key parameters:

- Viscosity grades:** ISO viscosity classes such as ISO VG 22, 32, 46, etc.
- Base oil type:** Mineral, synthetic, or semi-synthetic
- Additive package:** Corrosion inhibitors, anti-wear agents
- Compatibility notes:**

Elastomer compatibility, environmental considerations

**Equivalent brands and series:** From manufacturers like Shell, Chevron, Castrol, and others

The chart aims to match Mobilfluid 424's specifications with similar products to facilitate seamless substitutions.

**Deep Dive: Cross-Referencing Mobilfluid 424 with Other Lubricants**

**Major Brands and Their Equivalent Products**

Below are some common oils that are cross-referenced with Mobilfluid 424, categorized by viscosity grade:

**ISO VG 32**

Shell Tellus S2 M 32

Castrol Hyspin AWS 32

Chevron Rando HD 32

Fuchs Renolin ML 32

**ISO VG 46**

Shell Tellus S2 M 46

Castrol Hyspin AWS 46

Chevron Rando HD 46

Fuchs Renolin ML 46

**ISO VG 68**

Shell Tellus S2 M 68

Castrol Hyspin AWS 68

Chevron Rando HD 68

Fuchs Renolin ML 68

This list is not exhaustive but highlights the most common equivalents used in industries worldwide.

**Key Factors in Cross-Referencing**

When matching oils, consider:

- Viscosity grade:** Ensure the ISO VG matches
- Additive package:** Compatibility with system materials and performance requirements
- Base oil type:** Mineral vs. synthetic, especially for temperature and oxidative stability
- Certifications:** Compatibility with standards such as DIN 51524, ISO 6743, or OEM specifications
- Operating conditions:** Temperature range, pressure, and load

**Challenges and Limitations in Cross-Referencing**

While cross-reference charts are invaluable, they have limitations:

- Variability in Additive Packages:** Different manufacturers may use proprietary additive formulations, which can affect:

  - Wear protection
  - Corrosion resistance
  - Compatibility with seals and elastomers

- Differences in Base Oil Quality:** Even within the same viscosity grade, base oils can vary:

  - Mineral oils may have different refining processes
  - Synthetic oils might differ in chemical composition and performance

- Certification and Standards Compliance:** Not all equivalent oils meet the same industry standards, which can impact warranty and safety considerations.
- Environmental and Regulatory Factors:** Some oils are formulated to meet eco-friendly standards (e.g., biodegradable or low toxicity), which may influence cross-reference choices.

**Practical Applications and Case Studies**

**Case Study 1: Transitioning from Mobilfluid 424 to Alternative Brands**

A manufacturing plant faced a supply chain disruption, prompting a switch from Mobilfluid 424 to a locally available equivalent. Using the cross-reference chart:

- They identified a Shell Tellus S2 M 46 as an optimal match
- Conducted compatibility tests confirming seal and material compatibility
- Monitored system performance over 30 days, noting no adverse effects

This case underscores the importance of thorough cross-referencing and testing before full-scale implementation.

**Case Study 2: Retrofitting Hydraulic Systems for Better Performance**

An aerospace maintenance facility sought higher oxidation stability. They referenced Mobilfluid 424 and identified synthetic equivalents such as Fuchs Renolin ML 46. After testing:

- Improved thermal stability
- Reduced oil consumption
- Extended drain intervals

This example illustrates how cross-referencing can lead to performance improvements.

**Best Practices for Using Cross-Reference Charts**

To maximize the benefits of cross-reference charts, consider the following:

- Verify Technical Data Sheets (TDS):** Always compare detailed specs.
- Consult OEM Recommendations:** Ensure substitutions meet manufacturer standards.
- Perform Compatibility Testing:** Test on small samples before full deployment.
- Monitor System Performance:** Observe for leaks, wear, or deposit formation.
- Document Changes:** Maintain records for future reference and warranty purposes.

**Future Trends and Developments**

The lubricant industry is evolving, with trends including:

- Biodegradable and environmentally friendly oils:** Increasing cross-reference options for eco-conscious applications.
- Synthetic and semi-synthetic advancements:** Offering higher

performance and broader temperature ranges. Standardization efforts: Enhanced compatibility charts aligned with international standards. As these developments unfold, the importance of accurate and detailed cross-reference charts like the Mobilfluid 424 oil cross reference chart will only grow. Conclusion Understanding the Mobilfluid 424 oil cross reference chart is essential for professionals seeking reliable substitutes without compromising system integrity. Through meticulous comparison of viscosity grades, additive packages, and certifications, industry stakeholders can make informed choices that enhance performance, reduce costs, and ensure compliance. While challenges such as proprietary formulations and base oil differences exist, diligent research and testing can mitigate risks. In an industry where machinery uptime and safety are critical, leveraging detailed cross-reference charts is more than a convenience? it's a necessity. As the lubricant landscape continues to evolve, staying informed and adaptable remains the key to optimal operational excellence. Disclaimer: Always consult with lubricant manufacturers or technical experts before substituting oils, and adhere to OEM specifications and industry standards to ensure system compatibility and safety.

## QuestionAnswer

What is the purpose of a Mobilfluid 424 oil cross reference chart?

A Mobilfluid 424 oil cross reference chart helps identify equivalent oils from different brands or specifications, ensuring compatibility and optimal performance when replacing or selecting lubricants.

How do I use a Mobilfluid 424 oil cross reference chart effectively?

You can use the chart by matching the Mobilfluid 424 specifications with other brands' oil grades, checking properties like viscosity, API ratings, and performance standards to find suitable alternatives.

What are common brands that cross-reference with Mobilfluid 424 oil?

Common brands include Shell, Castrol, Texaco, Chevron, and Valvoline, among others. The cross-reference chart helps identify equivalent oils across these brands.

Is Mobilfluid 424 oil suitable for all types of machinery?

Mobilfluid 424 is designed for specific industrial applications; always check the machinery manufacturer's recommendations and the cross reference chart to ensure compatibility.

Where can I find a reliable Mobilfluid 424 oil cross reference chart?

Reliable charts can typically be found on the official Mobil website, authorized lubricant distributors, or industry-specific technical resources and catalogs.

What are the key specifications to look for when cross-referencing Mobilfluid 424 oil?

Key specifications include viscosity grade, API service classification, additive package, and compatibility with equipment materials.

Can I mix Mobilfluid 424 oil with other oils based on the cross reference chart?

It is generally not recommended to mix different oils without consulting technical guidelines, as mixing incompatible oils can affect performance and equipment safety.

How often should I consult a Mobilfluid 424 oil cross reference chart?

Use the chart whenever you need to replace or upgrade your lubricant to ensure you select a compatible and optimal alternative, especially when switching brands or specifications.

Related keywords: mobilfluid 424, oil cross reference, hydraulic oil chart, MobilFluid 424 substitute, hydraulic fluid comparison, oil compatibility chart, MobilFluid 424 equivalent, hydraulic lubricant cross reference, industrial oil chart, fluid identification guide

## **New holland 134 hydraulic oil equivalent**

new holland 134 hydraulic oil equivalent is a critical specification for maintaining optimal performance and longevity of New Holland agricultural equipment. Selecting the right hydraulic oil ensures smooth operation, reduces wear and tear, and prevents costly repairs. If you're looking for the best alternative to New Holland 134 hydraulic oil, understanding its properties, compatible substitutes, and maintenance tips is essential. This comprehensive guide will explore everything you need to know about the New Holland 134 hydraulic oil equivalent, helping you make informed decisions for your machinery.

**Understanding New Holland 134 Hydraulic Oil**

What Is New Holland 134 Hydraulic Oil? New Holland 134 hydraulic oil is a specially formulated hydraulic fluid designed for use in New Holland equipment. It meets specific standards to provide high lubricity, thermal stability, and corrosion resistance. This oil is engineered to operate efficiently under high-pressure conditions typical in agricultural machinery, ensuring reliable performance across various tasks.

**Key**

Properties of New Holland 134 Hydraulic Oil

**Viscosity:** Maintains optimal flow at different temperatures, usually around 10W-30 or similar grades.

**Additive Package:** Contains anti-wear, anti-corrosion, and anti-oxidation additives.

**Thermal Stability:** Resists breakdown under high operating temperatures.

**Compatibility:** Suitable for use with various hydraulic system components, including seals and filters.

**Why Is It Important to Find a Hydraulic Oil Equivalent?** Using the correct hydraulic oil equivalent is vital for several reasons:

**Cost-Effectiveness:** Some alternatives may be more affordable without sacrificing performance.

**Availability:** Genuine New Holland oils may not always be readily available; substitutes ensure continuous operation.

**Maintenance Flexibility:** Compatible oils can extend equipment lifespan and reduce downtime.

**Environmental Considerations:** Some equivalents are formulated to be more environmentally friendly.

**Hydraulic Oil Equivalents to New Holland 134**

**Common Alternatives and Their Characteristics**

When looking for a hydraulic oil equivalent to New Holland 134, consider the following options:

**ISO 32 or ISO 46 Hydraulic Oil:** These are standard viscosity grades suitable for many hydraulic systems. They typically contain anti-wear additives similar to New Holland 134.

**Mobil DTE 24:** A premium hydraulic oil with excellent thermal stability and anti-wear properties, compatible with most agricultural machinery.

**Shell Tellus S2 MX 46:** Known for its high-quality additive package and oxidation stability, suitable as an alternative.

**Caterpillar Hydraulic Oil TO-4 or TO-2:** Widely used in heavy machinery, these oils meet many of the same standards as New Holland 134.

**Rotella T6 Synthetic Hydraulic Oil:** Synthetic options offer enhanced performance in extreme temperatures and extended oil change intervals.

**Factors to Consider When Choosing a Hydraulic Oil Equivalent**

**Viscosity Grade:** Ensure the substitute matches the viscosity rating recommended by New Holland.

**Additive Compatibility:** Check for anti-wear, anti-corrosion, and anti-oxidation additives.

**Temperature Range:** Select an oil suitable for your operational climate.

**Compatibility with Seals and Materials:** Confirm the oil won't degrade rubber or plastic parts in your hydraulic system.

**Manufacturer Recommendations:** Always verify if the alternative meets or exceeds OEM specifications.

**Standards and Specifications to Look For**

**Understanding Hydraulic Oil Standards**

Hydraulic oils are classified according to international standards to ensure quality and performance:

**ISO 11158:** Specifies performance requirements for hydraulic oils.

**DENISON HF-0, HF-2, HF-1:** American standards for hydraulic fluids with varying anti-wear properties.

**OEM Certifications:** Many manufacturers, including New Holland, recommend oils that meet certain specifications or approvals.

**Matching the Standard to Your Needs**

For agricultural equipment like New Holland tractors, an ISO 32 or ISO 46 grade with compatible additives is often suitable. For high-temperature or high-pressure applications, synthetic oils like Rotella T6 may be preferable. Always consult your equipment manual for specific oil standards and ensure your chosen equivalent meets those requirements.

**How to Properly Select and Use Hydraulic Oil Equivalents**

**Step-by-Step Selection Process**

1. Identify the exact viscosity grade recommended by your equipment manual.

2. Check the existing hydraulic system for compatibility with the additive package.

3. Compare the specifications of potential substitutes to ensure they meet OEM standards.

4. Consider environmental factors, such as operating temperature and humidity.

5. Consult with a professional or the equipment manufacturer if unsure about compatibility.

**Best Practices for Using Hydraulic Oil Equivalents**

**Regular Inspection:** Periodically check for leaks, discoloration, or unusual noises.

**Oil Change Intervals:** Follow manufacturer recommendations, but consider more frequent

changes if operating conditions are severe. **Filters and Seals:** Replace hydraulic filters regularly and inspect seals for wear. **Record Keeping:** Maintain logs of oil changes and maintenance activities to monitor system health. **Potential Risks of Using Incorrect Hydraulic Oil** Using an oil that does not meet the required standards can lead to: **Reduced Hydraulic Efficiency:** Poor lubrication leads to increased wear and energy consumption. **Seal Swelling or Deterioration:** Incompatible oils can cause seals to swell or crack, leading to leaks. **Corrosion and Oxidation:** Lack of proper additives may result in rust and sludge buildup. **Overheating:** Inadequate thermal stability could cause the system to overheat, damaging components. **Shortened Equipment Lifespan:** Overall, using the wrong oil accelerates wear and decreases operational life. **Conclusion:** Ensuring Optimal Performance with the Right Hydraulic Oil Choosing the correct hydraulic oil equivalent to New Holland 134 is essential for maintaining the efficiency and longevity of your agricultural equipment. By understanding the key properties, standards, and compatibility factors, you can select a high-quality substitute that meets your operational needs. Always prioritize oils that conform to industry standards and OEM specifications to avoid potential damages. Regular maintenance, proper oil selection, and adherence to best practices will ensure your machinery performs reliably season after season. **Additional Tips and Resources** Consult your equipment manual for specific oil recommendations. Contact authorized New Holland dealerships or service centers for verified oil products. Consider synthetic oils for extended service intervals and better performance in extreme conditions. Stay informed about new hydraulic oil formulations and standards to optimize your equipment's performance. By following these guidelines, you can confidently select the best hydraulic oil equivalent for your New Holland machinery, ensuring smooth operation, reduced downtime, and maximum productivity.

**New Holland 134 Hydraulic Oil Equivalent: An In-Depth Review** When it comes to maintaining the optimal performance and longevity of your New Holland machinery, choosing the right hydraulic oil is paramount. Among the many options available, New Holland 134 Hydraulic Oil has gained considerable popularity among operators and service technicians alike. However, understanding its specifications, alternatives, and compatibility is essential for ensuring your equipment runs smoothly and efficiently. In this comprehensive review, we delve into what makes New Holland 134 hydraulic oil unique, explore suitable equivalents, and provide guidance on selecting the best hydraulic fluid for your needs. **Understanding New Holland 134 Hydraulic Oil** What is New Holland 134 Hydraulic Oil? New Holland 134 hydraulic oil is a specially formulated lubricant designed for use in a variety of New Holland agricultural and construction equipment. It is engineered to provide: **Excellent hydraulic system protection** **Optimal lubrication of hydraulic components** **Resistance to wear and oxidation** **Compatibility with seals and other system materials** This hydraulic oil conforms to specific standards and specifications established by New Holland, ensuring that it meets the operational demands of their machinery. **Key Specifications and Features** **Viscosity Grade:** Typically, New Holland 134 hydraulic oil is classified as an ISO 32 or 46 grade, indicating its viscosity level at operating temperatures. **Additive Package:** Formulated with anti-wear, anti-oxidation, anti-corrosion,

and anti-foaming agents to prolong hydraulic system life. Temperature Range: Suitable for a wide temperature spectrum, maintaining fluidity in cold weather and stability in high temperatures. Compatibility: Compatible with seals, hoses, and other materials used in New Holland machinery. Applications of New Holland 134 Hydraulic Oil Tractors and harvesters Loaders and backhoes Construction equipment Other hydraulic-driven machinery Proper use ensures efficient operation, minimizes downtime, and extends the lifespan of hydraulic components. Why Consider Hydraulic Oil Equivalents? While New Holland 134 hydraulic oil is tailored for specific machinery, there are circumstances where an operator might need an alternative: Availability Issues: Local suppliers may not stock New Holland-branded oil. Cost Considerations: Some equivalents may offer similar performance at a reduced price. Operational Compatibility: Certain machinery might specify a hydraulic oil with a different brand or formulation but similar specifications. Maintenance and Flexibility: Using compatible equivalents allows for easier inventory management. However, selecting an equivalent should be done carefully, ensuring it matches or exceeds the performance standards required for your equipment.

Hydraulic Oil Equivalents to New Holland 134

Key Criteria for Equivalents

When choosing a hydraulic oil that serves as an equivalent to New Holland 134, consider the following parameters:

Viscosity Grade: Should match the ISO 32 or 46 grade, depending on your machinery specifications.

Additive Package: Must contain anti-wear, anti-oxidation, anti-corrosion, and anti-foaming additives.

Compliance with Industry Standards: Look for oils conforming to ISO 11158, DIN 51524, or API classifications.

Compatibility: Should be compatible with seals and materials used in your equipment.

Temperature Performance: Should perform reliably within your operational temperature range.

Popular Hydraulic Oil Equivalents

Below are some commonly recommended equivalents to New Holland 134 hydraulic oil:

Shell Tellus S2 VX 32 / 46

Description: A high-performance mineral hydraulic oil designed for demanding applications.

Standards: Meets ISO 11158 HV, DIN 51524 Part 3, and API CK-4.

Features: Excellent wear protection, oxidation stability, and low-temperature performance.

Compatibility: Suitable for a wide range of hydraulic systems, including those similar to New Holland.

Total Hydraulic HT 32 / 46

Description: Mineral hydraulic oil with anti-wear properties.

Standards: Complies with ISO 11158 HV and DIN 51524.

Features: Good thermal stability, oxidation resistance, and compatibility with seals.

Application: Suitable for agricultural, construction, and industrial machinery.

Mobil DTE 11M 32 / 46

Description: Mineral-based hydraulic oil with synthetic additives.

Standards: Meets or exceeds ISO 11158 HV and API CK-4.

Features: Exceptional oxidation stability, wear protection, and filterability.

Compatibility: Well-suited for hydraulic systems requiring high-performance oils.

Chevron Hydraulic Oil AW 32 / 46

Description: Fully formulated anti-wear hydraulic oil.

Standards: Meets ISO 11158 HV and other industry standards.

Features: Superior anti-wear protection, corrosion resistance, and thermal stability.

Use Cases: Appropriate for agricultural and construction equipment.

Yale Hydraulic Oil AW 32 / 46

Description: Hydraulic oil designed specifically for heavy-duty machinery.

Standards: Complies with ISO 11158 HV.

Features: Good wear protection, oxidation resistance, and compatibility with various seals.

Application: Suitable for machinery similar to New Holland models.

Comparing Equivalents to New Holland 134

When selecting an equivalent hydraulic oil, it's crucial to compare specifications carefully:

| Parameter | New Holland 134 | Shell Tellus S2 VX | Total Hydraulic HT | Mobil DTE 11M | Chevron AW | Yale Hydraulic |
|-----------|-----------------|--------------------|--------------------|---------------|------------|----------------|
|-----------|-----------------|--------------------|--------------------|---------------|------------|----------------|

||-----|-----|-----|-----|-----|-----|-----||

Viscosity | ISO 32/46 | ISO 32/46 | ISO 32/46 | ISO 32/46 | ISO 32/46 | ISO 32/46 || Standards | New Holland | ISO 11158 HV | ISO 11158 HV | ISO 11158 HV | ISO 11158 HV | ISO 11158 HV || Additives | Yes | Yes | Yes | Yes | Yes | Yes || Temperature Range | Wide | Wide | Wide | Wide | Wide | Wide || Compatibility | High | High | High | High | High | High |

Choosing an equivalent that aligns with these parameters ensures your machinery remains protected and operates efficiently.

Installation and Maintenance Tips for Hydraulic Oils

Proper handling and maintenance of hydraulic fluids are vital for performance and longevity:

Fluid Change Intervals: Follow manufacturer recommendations, generally every 2,000 to 4,000 hours of operation or annually.

Filtration: Keep hydraulic systems well-filtered to prevent contamination.

Storage: Store hydraulic oils in sealed, clean containers away from temperature extremes and contaminants.

Compatibility Checks: Before switching to an equivalent, verify compatibility with your machinery's seals and materials.

Monitoring: Regularly check for signs of oil degradation such as discoloration, foaming, or unusual viscosity changes.

Conclusion: Making the Right Choice

The New Holland 134 hydraulic oil equivalent offers a practical solution for operators seeking reliable, high-performance hydraulic fluids compatible with their machinery. While genuine New Holland oils provide assurance of perfect compatibility and performance, high-quality equivalents like Shell Tellus S2 VX, Total Hydraulic HT, and Mobil DTE 11M can serve as effective substitutes when properly matched to the required specifications. Always prioritize oils that meet or exceed industry standards, possess appropriate viscosity grades, and are formulated with suitable additive packages. Proper maintenance, monitoring, and adherence to manufacturer guidelines will ensure your hydraulic system remains efficient, durable, and cost-effective over its lifespan.

By understanding the nuances of hydraulic oil specifications and carefully selecting the right equivalent, operators can optimize machinery performance, reduce downtime, and extend the operational life of their equipment.

Note: Always consult your equipment's manual or a hydraulic specialist before switching oils or using equivalents to ensure compatibility and maintain warranty coverage.

QuestionAnswer

What is the recommended hydraulic oil for a New Holland 134 tractor?

The recommended hydraulic oil for a New Holland 134 tractor is typically a quality hydraulic fluid that meets or exceeds API GL-4 or GL-5 specifications, such as JD Hy-Gard or equivalent hydraulic oils suitable for the tractor's operating conditions.

Is there a specific hydraulic oil viscosity recommended for the New Holland 134?

Yes, generally a hydraulic oil with a viscosity grade of ISO VG 46 or 68 is suitable for the New Holland 134, but always refer to the owner's manual for the precise viscosity recommendation based

on ambient temperature.

Can I use universal hydraulic oils as an equivalent for the New Holland 134?

Universal hydraulic oils that meet the required specifications (API GL-4 or GL-5, ISO VG 46/68) can be used as equivalents, but it's important to verify compatibility with the tractor's hydraulic system to prevent damage.

What are the signs that my New Holland 134 hydraulic oil needs to be replaced or topped up?

Signs include reduced hydraulic performance, unusual noises, increased operating temperatures, or visible contamination. Regularly checking the oil level and condition can help determine when replacement or topping up is necessary.

Where can I find an equivalent hydraulic oil for the New Holland 134 if the original is unavailable?

You can find equivalent hydraulic oils at tractor supply stores, authorized New Holland dealerships, or reputable online retailers, ensuring the oil meets the specified performance standards and viscosity for your tractor.

Related keywords: New Holland 134 hydraulic oil, hydraulic fluid alternative, hydraulic oil substitute, NH 134 fluid replacement, hydraulic oil equivalent, tractor hydraulic fluid, New Holland hydraulic oil, hydraulic oil comparison, hydraulic fluid specs, NH 134 oil similar

## Shell tellus c22

**Introduction to Shell Tellus C22: The Premium Hydraulic Oil Solution**shell tellus c22 is a leading hydraulic oil formulation designed to meet the demanding needs of modern industrial machinery. As industries evolve, the importance of reliable, high-performance lubricants becomes paramount to ensure equipment longevity, efficiency, and safety. Shell Tellus C22 stands out as a top-tier hydraulic oil that combines advanced additive technology with high-quality base oils, providing optimal performance across a variety of applications. Whether in manufacturing plants, construction equipment, or mobile machinery, Shell Tellus C22 offers a comprehensive solution to enhance operational productivity and reduce maintenance costs. In this comprehensive guide, we will delve into the key features, benefits, applications, and technical specifications of Shell Tellus C22, helping you make an informed decision for your hydraulic system needs. **Understanding Hydraulic Oils and Their Importance**What Are Hydraulic Oils?Hydraulic oils are specialized lubricants used in hydraulic

systems to transfer power efficiently, lubricate moving parts, and prevent corrosion and wear. They are vital in ensuring the smooth operation of machinery such as excavators, presses, injection molding machines, and other industrial equipment.

### Why Quality Matters in Hydraulic Oils

Using high-quality hydraulic oils like Shell Tellus C22 ensures:

- Reduced equipment wear and tear
- Improved system efficiency
- Lower maintenance costs
- Enhanced safety and reliability
- Extended machinery lifespan

Choosing the right hydraulic oil is crucial to prevent issues such as foaming, oxidation, and deposit formation, which can impair system performance.

### Features and Benefits of Shell Tellus C22

#### Key Features

- High-Performance Additive Technology:** Shell Tellus C22 contains advanced additives that provide excellent wear protection and oxidation stability.
- Premium Base Oils:** Made from carefully selected base oils to ensure low volatility and high thermal stability.
- Anti-Wear and Anti-Corrosion Properties:** Protects hydraulic components from premature wear and corrosion.
- Excellent Demulsibility:** Ensures rapid separation of water from the oil, reducing the risk of emulsions.
- Good Compatibility:** Compatible with many sealing materials and other lubricants, minimizing system contamination.

#### Major Benefits

- Enhanced Equipment Durability:** Provides robust protection for hydraulic components, extending service intervals.
- Superior Hydraulic Performance:** Maintains optimal viscosity for efficient power transfer.
- Reduced Operating Costs:** Less downtime and lower maintenance expenses due to improved reliability.
- Environmental Compatibility:** Meets industry standards for environmental safety and sustainability.
- Versatility:** Suitable for a wide range of hydraulic systems operating under various temperature and load conditions.

### Technical Specifications of Shell Tellus C22

| Parameter             | Specification                                                   |
|-----------------------|-----------------------------------------------------------------|
| Viscosity Grade       | ISO 32 and ISO 46 (depending on application)                    |
| Viscosity Index       | Typically above 100                                             |
| Flash Point           | Generally above 200°C                                           |
| Pour Point            | Typically below -15°C                                           |
| Oxidation Stability   | Excellent, ensuring long oil life                               |
| Anti-Wear Performance | Meets or exceeds industry standards such as DIN 51524 Part 2    |
| Compatibility         | Compatible with most sealing materials and other hydraulic oils |

**Note:** Always refer to the product datasheet for detailed specifications tailored to your specific application.

### Applications of Shell Tellus C22

Shell Tellus C22 is designed to deliver optimal performance in various industrial and mobile hydraulic systems. Its versatility makes it suitable for:

- Industrial Hydraulic Systems**
  - Manufacturing machinery
  - Injection molding equipment
  - Presses and stamping machines
  - Machine tools
- Mobile Hydraulic Equipment**
  - Construction machinery (excavators, loaders)
  - Agricultural machinery
  - Material handling equipment
  - Mining equipment
- Specialized Uses**
  - Hydraulic systems requiring long oil life
  - Equipment operating under high load and temperature conditions
  - Systems demanding high wear protection

### Why Choose Shell Tellus C22 Over Other Hydraulic Oils?

**Superior Performance and Reliability** Shell Tellus C22 is formulated with proprietary additives that outperform many conventional hydraulic oils, ensuring your equipment runs smoothly and efficiently.

**Proven Track Record** With decades of experience in lubricant formulation, Shell offers products backed by extensive research, testing, and real-world performance data.

**Environmental and Safety Standards** Shell is committed to sustainability, and Tellus C22 complies with industry standards for environmental safety, making it a responsible choice for modern facilities.

**Cost-Effectiveness** The durability and efficiency benefits of Shell Tellus C22 translate into reduced maintenance costs and minimized downtime, providing excellent value over the product's lifespan.

### How to Properly Use and Maintain Shell Tellus C22

#### Application Guidelines

Ensure the

hydraulic system is clean before filling. Use the recommended viscosity grade (ISO 32 or ISO 46) based on your equipment specifications. Follow the manufacturer's instructions for oil change intervals. Regularly monitor oil condition and viscosity to detect early signs of contamination or degradation.

**Storage Recommendations** Store in a clean, dry, and cool environment. Keep containers tightly sealed when not in use. Avoid exposure to direct sunlight and extreme temperatures to preserve oil quality.

**Environmental and Safety Considerations** Shell Tellus C22 is formulated to meet stringent safety and environmental standards. Proper handling and disposal are essential to minimize environmental impact. Always follow local regulations and best practices for lubricant disposal.

**Conclusion: Making the Most of Shell Tellus C22** Choosing the right hydraulic oil is vital for maintaining the efficiency, safety, and longevity of your machinery. Shell Tellus C22 stands out as an industry-leading solution, offering exceptional performance, reliability, and value. Its advanced formulation ensures optimal protection against wear, oxidation, and corrosion, making it suitable for a wide range of industrial and mobile hydraulic applications. Investing in Shell Tellus C22 can lead to significant operational benefits, including extended equipment life, reduced downtime, and lower maintenance costs. For businesses seeking a dependable, high-quality hydraulic oil, Shell Tellus C22 is an excellent choice that aligns with industry standards and environmental considerations.

**Where to Purchase Shell Tellus C22** Shell products are widely available through authorized distributors, industrial supply stores, and online platforms. When purchasing Shell Tellus C22, ensure you buy from reputable sources to guarantee product authenticity and quality.

**Final Thoughts** In summary, Shell Tellus C22 is a premium hydraulic oil designed to meet the rigorous demands of modern machinery. Its blend of high-quality base oils and advanced additives provides unparalleled protection and performance, making it a smart investment for any industrial operation aiming for efficiency and durability. For more information or to request a quote, contact your local Shell representative or visit the official Shell website. Proper selection and maintenance of hydraulic oils like Shell Tellus C22 will ensure your equipment operates smoothly, safely, and efficiently for years to come.

**Shell Tellus C22: An In-Depth Review of a Premier Hydraulic Oil Solution** In the realm of industrial machinery and hydraulic systems, the choice of lubricants plays a pivotal role in ensuring operational efficiency, longevity, and safety. Among the myriad options available, Shell Tellus C22 stands out as a premium hydraulic oil designed to meet the demanding needs of modern machinery. This comprehensive review delves into the composition, features, applications, and performance characteristics of Shell Tellus C22, offering industry professionals and enthusiasts a detailed understanding of this product.

**Understanding Shell Tellus C22** What is Shell Tellus C22? Shell Tellus C22 is a high-performance, anti-wear hydraulic oil formulated to deliver exceptional lubrication, oxidation stability, and wear protection. It belongs to Shell's renowned Tellus series, which is widely recognized across industries for reliable hydraulic system performance. C22 indicates its viscosity grade, aligning with ISO 32 or ISO 46 standards, depending on regional classifications, making it suitable for a broad spectrum of hydraulic applications.

**Key Attributes and Specifications** Viscosity

Grade: ISO VG 32/46, adaptable for various machinery requirements. Base Oil Composition: Mineral oil-based, with carefully selected additives. Additive Technology: Incorporates anti-wear agents, rust and oxidation inhibitors, and rust inhibitors. Performance Standards: Meets or exceeds industry standards such as DIN 51524 Part 2, ISO 11158, and API GL-1.

### Composition and Technology

#### Base Oil Characteristics

Shell Tellus C22 utilizes high-quality mineral oils that provide excellent lubricating properties. These base oils are refined to remove impurities, ensuring consistent viscosity and thermal stability. The mineral oil base offers reliable performance across a range of operational temperatures, though it is primarily designed for moderate to heavy-duty applications.

#### Advanced Additive Package

The additive technology embedded within Shell Tellus C22 enhances its performance attributes:

- Anti-wear agents:** Protect moving parts from premature wear, extending equipment lifespan.
- Oxidation inhibitors:** Prevent oil degradation during prolonged operation, reducing sludge and deposit formation.
- Rust and corrosion inhibitors:** Safeguard hydraulic components against moisture-induced corrosion.
- Demulsifiers:** Facilitate efficient separation of water from oil, minimizing contamination risks.

This combination results in a lubricant that maintains its protective qualities under demanding operational conditions.

### Performance Features and Benefits

#### Enhanced Wear Protection

One of Shell Tellus C22's primary advantages is its ability to form a durable lubricating film on metal surfaces, minimizing metal-to-metal contact. This reduces component wear, especially in high-load systems, and ensures machinery operates smoothly over extended periods.

#### Oxidation and Thermal Stability

The oil's resistance to oxidation minimizes the formation of sludge, varnish, and acid buildup. Its thermal stability allows it to withstand high operating temperatures without significant breakdown, maintaining viscosity and lubrication efficacy.

#### Corrosion Resistance and Water Separation

The rust and corrosion inhibitors protect hydraulic components from moisture-induced deterioration. Additionally, efficient demulsification properties facilitate water separation, reducing the risk of hydraulic system failure due to water contamination.

#### Energy Efficiency and Cost Savings

By reducing wear and maintaining optimal viscosity, Shell Tellus C22 can contribute to lower energy consumption, reducing operational costs over time. Its long service life also diminishes maintenance frequency and expenses.

### Applications and Compatibility

#### Industrial Hydraulic Systems

Shell Tellus C22 is suitable for a wide range of industrial machinery, including:

- Plastic moulding machines
- Construction equipment
- Manufacturing presses
- Material handling systems

Its versatility makes it a preferred choice across sectors like manufacturing, mining, and transportation.

#### Compatibility with Equipment

This hydraulic oil is compatible with most hydraulic system materials, including seals, hoses, and pumps. However, it is crucial to consult equipment manufacturer guidelines to ensure compatibility, especially with systems that have specific lubricant requirements.

#### Operational Conditions

While Shell Tellus C22 performs reliably under typical conditions, it is especially advantageous in:

- Moderate to high-temperature environments
- Systems requiring anti-wear protection
- Applications with frequent water exposure

#### Comparison with Other Hydraulic Oils

##### Versus Mineral Oils

Compared to standard mineral oils, Shell Tellus C22 offers superior additive technology, resulting in better wear protection, oxidation stability, and water separation. Its formulation extends oil change intervals and reduces maintenance.

##### Versus Synthetic Alternatives

Synthetic hydraulic oils generally provide better performance in extreme temperatures and longer service life. However, Shell Tellus C22 strikes a

balance between cost and performance, making it an economical choice for many applications without compromising essential protective features.

### Market Positioning

Shell Tellus C22 is positioned as a premium mineral hydraulic oil, suitable for applications where reliability and protection are paramount but where synthetic oils may not be economically justified.

### Operational and Maintenance Considerations

#### Oil Change Intervals

The oil's stability allows for extended drain intervals, typically ranging from 1,000 to 2,000 hours of operation, depending on system conditions and load.

#### Monitoring and Testing

Regular analysis of oil condition—checking parameters such as viscosity, particle contamination, and water content—helps optimize maintenance schedules and prevent system failures.

#### Storage and Handling

Proper storage in sealed containers away from contaminants ensures the oil maintains its quality. Handling precautions include avoiding exposure to moisture and extreme temperatures.

### Sustainability and Environmental Impact

#### Environmental Considerations

Shell Tellus C22, like other mineral oils, poses environmental risks if spilled or improperly disposed of. However, Shell emphasizes responsible handling, and the product's formulation aims to minimize environmental impact during its lifecycle.

#### Recycling and Disposal

Disposal of used oil must adhere to local regulations. Recycling options are available, and Shell provides guidance to ensure environmentally responsible practices.

### Conclusion: Is Shell Tellus C22 the Right Choice?

Shell Tellus C22 embodies a blend of technological innovation, reliable performance, and cost-effectiveness, making it a compelling option for a wide range of hydraulic systems. Its advanced additive package ensures superior wear protection, oxidation resistance, and water separation, which are crucial for maintaining machinery efficiency and longevity. For industries seeking a high-quality hydraulic oil that balances performance with economic considerations, Shell Tellus C22 offers a dependable solution. Its compatibility with various equipment and operational environments further enhances its appeal. Ultimately, selecting the right hydraulic oil depends on specific system requirements and operational conditions. However, Shell Tellus C22's proven track record and comprehensive performance features position it as a top contender in the field of industrial lubricants.

**Disclaimer:** Always consult manufacturer specifications and technical datasheets before selecting or replacing hydraulic oils to ensure compatibility and optimal performance.

## QuestionAnswer

What are the key features of the Shell Tellus C22 hydraulic oil?

Shell Tellus C22 is a high-performance hydraulic oil designed to provide excellent lubrication, corrosion protection, and oxidation stability, suitable for a wide range of industrial hydraulic systems.

Is Shell Tellus C22 compatible with other hydraulic oils?

Shell Tellus C22 is formulated to meet specific specifications and can generally be used in systems

requiring ISO 32 hydraulic oils. However, it's recommended to consult equipment manufacturer guidelines before mixing with other oils.

What applications are best suited for Shell Tellus C22?

Shell Tellus C22 is ideal for industrial hydraulic systems, including manufacturing machinery, mobile equipment, and other applications where high performance and protection are required.

How does Shell Tellus C22 contribute to equipment longevity?

By providing excellent anti-wear properties, oxidation stability, and corrosion protection, Shell Tellus C22 helps extend the lifespan of hydraulic components and reduces maintenance costs.

What are the storage recommendations for Shell Tellus C22?

Store Shell Tellus C22 in a cool, dry, and well-ventilated area, away from direct sunlight and incompatible materials. Ensure containers are tightly sealed to prevent contamination.

Where can I purchase Shell Tellus C22 hydraulic oil?

Shell Tellus C22 can be purchased through authorized Shell distributors, industrial supply stores, or directly from Shell's official channels. It's recommended to buy from reputable sources to ensure product authenticity.

Related keywords: shell tellus c22, engine oil, motor oil, synthetic oil, vehicle lubrication, automotive oil, engine maintenance, car oil specifications, motor oil brands, engine performance

## Shell tellus c 220

shell tellus c 220 is a premium quality grease formulated specifically for demanding industrial and automotive applications. Known for its exceptional performance, durability, and resistance to extreme conditions, Shell Tellus C 220 is an essential lubricant for machinery that requires reliable and long-lasting grease solutions. In this comprehensive guide, we will explore everything you need to know about Shell Tellus C 220, including its features, applications, benefits, and how it compares to other lubricants on the market. What is Shell Tellus C 220? Shell Tellus C 220 is a high-performance, calcium sulfonate complex grease designed for use in a variety of industrial and automotive applications. It is formulated with advanced thickening agents and high-quality base oils

to provide excellent lubrication under challenging conditions. Its consistency, denoted by a NLGI grade of 2, makes it suitable for a wide range of uses where a stable, long-lasting grease is required.

**Key Features of Shell Tellus C 220**

- Exceptional Wear Protection:** Reduces equipment wear and prolongs machinery life.
- High Resistance to Water Washout:** Maintains lubrication integrity even in wet environments.
- Excellent Oxidation Stability:** Ensures long service life without breakdown.
- Outstanding Thermal Stability:** Performs reliably at high temperatures, preventing softening or melting.
- Corrosion and Rust Inhibition:** Protects metal surfaces from corrosion.
- Good Mechanical Stability:** Resists thinning or separation during operation.

**Applications of Shell Tellus C 220**

Shell Tellus C 220 is versatile and suitable for a broad spectrum of applications, including:

- Industrial Equipment**
  - Gearboxes and gear drives
  - Bearings and sliding surfaces
  - Conveyor systems
  - Hydraulic systems requiring high load capacity
- Automotive Uses**
  - Wheel bearings
  - Suspension components
  - Steering systems
  - Drive shafts and CV joints
- Construction and Heavy Machinery**
  - Excavators and loaders
  - Crushers and bulldozers
  - Mining equipment

**Factors Influencing Application Choice**

When selecting Shell Tellus C 220, consider:

- Operating temperature ranges
- Load conditions
- Exposure to water or contaminants
- Maintenance schedules

**Benefits of Using Shell Tellus C 220**

Choosing Shell Tellus C 220 offers numerous advantages that enhance equipment performance and reduce operational costs:

- Enhanced Equipment Longevity:** The superior lubricating film reduces metal-to-metal contact, decreasing wear and extending machinery life.
- Operational Reliability:** Its stability under high loads and temperatures ensures consistent performance, minimizing unexpected downtimes.
- Cost-Effective Maintenance:** Long-lasting lubrication reduces the frequency of re-greasing and maintenance interventions.
- Environmental Resistance:** High resistance to water washout and corrosion protection make it suitable for challenging environments.
- Energy Efficiency:** Reduces friction and energy consumption, contributing to lower operational costs.

**Technical Specifications of Shell Tellus C 220**

| Specification               | Details                                                           |
|-----------------------------|-------------------------------------------------------------------|
| NLGI Grade                  | 2                                                                 |
| Thickener                   | Calcium sulfonate complex                                         |
| Appearance                  | Smooth, homogeneous grease                                        |
| Base Oil Viscosity          | Varies depending on formulation, optimized for high load capacity |
| Operating Temperature Range | -20°C to +120°C (up to +140°C intermittently)                     |
| Water Resistance            | Excellent, resistant to washout                                   |

Understanding these specifications helps in selecting the right lubricant for specific machinery and operating conditions.

**How to Apply Shell Tellus C 220**

Proper application ensures maximum performance and lifespan of the grease. Follow these steps:

- Clean the surface:** Remove old grease, dirt, and moisture from the contact surfaces.
- Apply the grease:** Use appropriate tools like grease guns or spatulas to ensure even coverage.
- Lubrication intervals:** Follow manufacturer recommendations or monitor equipment for signs of wear or grease degradation.
- Re-greasing:** Reapply as necessary, especially in high-demand or contaminated environments.

**Storage and Handling Tips**

To maintain the quality and effectiveness of Shell Tellus C 220:

- Store in a cool, dry place away from direct sunlight.
- Keep containers sealed when not in use.
- Avoid contamination with dirt, water, or other foreign materials.
- Follow safety guidelines provided by Shell for handling and disposal.

**Comparison with Other Greases**

Understanding how Shell Tellus C 220 compares with other greases helps in making informed decisions:

- Versus Lithium-Based Greases:** Calcium sulfonate complex greases like Shell Tellus C 220 generally offer superior water resistance and load-carrying capacity compared to lithium greases.
- Better oxidation stability,** leading

to longer service intervals. **Versus Synthetic Greases** Synthetic lubricants often perform better at extreme temperatures. Shell Tellus C 220 provides a cost-effective solution with excellent performance in most industrial environments. **Versus Mineral Oil-Based Greases** Mineral oils are less stable and may require more frequent reapplication. Shell Tellus C 220's advanced formulation offers better longevity and protection. **Environmental and Safety Considerations** Shell takes environmental responsibility seriously. Shell Tellus C 220 is formulated to minimize environmental impact, but proper handling and disposal are essential: Avoid spills and leaks during application. Dispose of used grease in accordance with local regulations. Use personal protective equipment when handling to prevent skin or eye contact. **Conclusion** Shell Tellus C 220 stands out as a high-quality, reliable grease suitable for a wide array of industrial and automotive applications. Its advanced calcium sulfonate complex formulation ensures excellent wear protection, water resistance, and thermal stability, making it a top choice for demanding environments. Proper application, maintenance, and storage practices will maximize its benefits, contributing to the longevity and efficiency of your machinery. Whether you operate in manufacturing, construction, transportation, or heavy machinery sectors, Shell Tellus C 220 offers a cost-effective, high-performance lubrication solution. Investing in such quality lubricants not only enhances equipment performance but also reduces maintenance costs and downtime, ultimately supporting your operational efficiency and sustainability goals. For optimal results, always refer to the manufacturer's guidelines and consult with Shell technical representatives to select the best lubrication solutions tailored to your specific needs.

Shell Tellus C 220 is a high-quality hydraulic oil designed to meet the demanding needs of modern machinery and industrial applications. As a leading product in Shell's extensive range of lubricants, Shell Tellus C 220 offers a blend of advanced formulation, superior performance, and reliable protection for hydraulic systems. This review delves into the key features, benefits, applications, and considerations of Shell Tellus C 220, providing a comprehensive guide for engineers, maintenance professionals, and industry stakeholders seeking a dependable hydraulic oil. **Introduction to Shell Tellus C 220** Shell Tellus C 220 is a high-performance, mineral-based hydraulic oil formulated with advanced additive technology. It is designed to deliver excellent lubrication, oxidation stability, and wear protection across a wide range of hydraulic equipment. The "220" in its name indicates its ISO VG (Viscosity Grade), which corresponds to a viscosity of approximately 220 centistokes at 40°C, making it suitable for medium to high-pressure hydraulic systems. The oil is engineered to operate efficiently under varying temperature conditions, ensuring minimal system wear and extending equipment lifespan. Its formulation adheres to stringent industry standards, including ISO 11158 and various OEM specifications, ensuring compatibility and optimal performance in diverse application settings. **Key Features and Benefits** 1. **Excellent Viscosity Index** Maintains consistent viscosity over a wide temperature range, ensuring reliable hydraulic performance. Reduces the risk of hydraulic system malfunction due to viscosity fluctuation during startup or operation. 2. **Superior Oxidation and Thermal Stability** Resists oxidation, which can cause sludge and varnish formation, thus extending oil

and component life. Handles high operating temperatures without degradation, making it suitable for demanding applications.

**3. Effective Wear Protection** Equipped with advanced anti-wear additives that protect pumps, valves, and other hydraulic components. Helps reduce maintenance costs and prevent unexpected equipment failures.

**4. Compatibility and Versatility** Compatible with most hydraulic system materials, including seals and hoses. Suitable for a broad range of hydraulic machinery in sectors such as manufacturing, construction, marine, and mining.

**5. Environmental and Safety Aspects** Meets various industry standards for safety and environmental impact. Designed to minimize sludge and deposit formation, aiding in cleaner operation.

**Applications of Shell Tellus C 220** Shell Tellus C 220 is versatile and can be used in various hydraulic systems, including:

- Industrial machinery such as presses, injection molding machines, and CNC equipment.
- Mobile hydraulic systems in construction and agricultural equipment.
- Marine hydraulic systems requiring high-performance oils.
- Steel mills, mining equipment, and other heavy-duty industrial applications.

Its wide compatibility makes it a preferred choice for facilities with mixed equipment needing a reliable hydraulic fluid.

**Performance Standards and Approvals** Shell Tellus C 220 complies with and exceeds several industry and OEM standards, ensuring high performance and compatibility: ISO 11158 HM and HV classifications. Meets or exceeds specifications from major OEMs like Sauer-Danfoss, Bosch Rexroth, and Parker Hannifin. Suitable for use in systems requiring HLPD (Hydraulic Lubricant, Power Drive) specifications. These certifications assure users of its quality, reliability, and suitability for critical hydraulic applications.

**Advantages of Using Shell Tellus C 220**

- Extended Equipment Life:** Its robust anti-wear and anti-oxidation properties protect vital hydraulic components, reducing downtime.
- Operational Efficiency:** Stable viscosity and thermal stability promote smooth and efficient hydraulic system operation.
- Cost Savings:** Longer oil life and fewer repairs translate into lower maintenance costs.
- Environmental Compliance:** Meets environmental standards, reducing ecological impact when disposed of properly.
- Ease of Handling:** Clear specifications and compatibility ease procurement and maintenance procedures.

**Limitations and Considerations** While Shell Tellus C 220 offers many benefits, users should consider:

- Cost:** Premium formulations may have a higher initial purchase price compared to lower-grade oils.
- Compatibility Checks:** Always verify compatibility with specific equipment and seal materials to prevent leaks or damage.
- Storage Conditions:** Store in a cool, dry place away from direct sunlight to preserve oil integrity.
- Change Intervals:** Follow OEM recommendations for oil change intervals to maximize performance and lifespan.

**How to Choose the Right Hydraulic Oil** Selecting the appropriate hydraulic oil depends on several factors:

- Viscosity Grade:** Match the ISO VG (like 220) to your system's operating temperature and pressure requirements.
- Additive Compatibility:** Ensure the oil's additive package aligns with your equipment specifications.
- Environmental and Safety Standards:** Consider eco-friendly options if required.
- OEM Recommendations:** Always adhere to the manufacturer's specifications for optimal results.

**Conclusion** Shell Tellus C 220 stands out as a premium hydraulic oil that combines advanced technology with proven performance. Its excellent viscosity stability, oxidation resistance, and wear protection make it suitable for a wide array of industrial and mobile hydraulic systems. While it may involve a higher initial investment, the long-term benefits—such as extended equipment life, reduced maintenance, and operational efficiency—make it a valuable choice for industries aiming for reliable and efficient hydraulic system performance. In summary, Shell Tellus C 220 is a dependable,

versatile, and high-quality hydraulic fluid that meets the rigorous demands of modern machinery. Proper selection, handling, and maintenance ensure that users can maximize its benefits, ensuring smooth, efficient, and sustainable operation for years to come.

## QuestionAnswer

What are the key features of the Shell Tellus C 220 hydraulic oil?

Shell Tellus C 220 is a high-performance hydraulic oil designed for heavy-duty industrial equipment. It offers excellent wear protection, oxidation stability, and excellent low-temperature fluidity, ensuring reliable operation and extended equipment life.

Is Shell Tellus C 220 suitable for use in all types of hydraulic systems?

Shell Tellus C 220 is suitable for a wide range of hydraulic systems, especially those requiring ISO VG 220 oils. However, always check your equipment manufacturer's specifications to ensure compatibility before use.

How does Shell Tellus C 220 perform in high-temperature operating conditions?

Shell Tellus C 220 offers excellent oxidation stability and film strength, making it suitable for high-temperature applications. It helps prevent deposit formation and maintains system cleanliness during prolonged operation at elevated temperatures.

What are the benefits of using Shell Tellus C 220 over mineral-based hydraulic oils?

Compared to standard mineral oils, Shell Tellus C 220 provides improved wear protection, better thermal and oxidative stability, longer oil life, and enhanced equipment protection, leading to reduced maintenance costs and increased efficiency.

How should Shell Tellus C 220 be stored and handled?

Store Shell Tellus C 220 in a clean, dry, well-ventilated area away from direct sunlight and sources of heat. Ensure containers are sealed properly to prevent contamination. Handle with appropriate safety measures as outlined in the product's safety data sheet.

Related keywords: shell tellus c 220, gear oil, engine oil, motor oil, lubricants, automotive oil,

heavy-duty oil, synthetic oil, oil viscosity, machinery lubrication